



MAXAM

MS300

E-3/G-3/L-3

Light duty E-3/ L-3 lug pattern ideally suited to municipalities, small sand and aggregate operations and other smooth surface applications.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High-quality carcass allows for excellent retreadability
- Wear and cut-resistant tread compound

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load
				mm inch	mm inch	mm inch			kPa psi	km/h mph	kg lbs
15.5R25	**	TL	12.00/1.3	1274	389	24	E-3	160B	525	50	4500
				50.2	15.3	30			76	30	9900
							L-3	176A2	650	50	7100
									94	30	15700
17.5R25	**	TL	14.00/1.5	1346	440	25	E-3	167B	525	50	5450
				53	17.3	32			76	30	12000
							L-3	182A2	650	10	8500
									94	6	18700
20.5R25	**	TL	17.00/2.0	1493	524	28	E-3	177B	525	50	7300
				58.8	20.6	36			76	30	16100
							L-3	193A2	650	10	11500
									94	6	25400
23.5R25	**	TL	19.50/2.5	1605	601	32	E-3	185B	525	50	9250
				63.2	23.7	40			76	30	20400
							L-3	201A2	650	10	14500
									94	6	32000
26.5R25	**	TL	22.00/3.0	1739	669	35	E-3	193B	525	50	11500
				68.5	26.3	44			76	30	25400
							L-3	209A2	650	10	18500
									94	6	40800
29.5R25	**	TL	25.00/3.5	1866	751	38	E-3	200B	525	50	14000
				73.5	29.6	48			76	30	30900
							L-3	216A2	650	10	22400
									94	6	49400

