



**MAXAM**

**MS903**

**BACKHOE -  
INDUSTRIAL  
SERVICE**

Applications:



**Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.**

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Size	P.R.	Type	Rim	O.D.		T.D.	Infl. P.	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm			32nds mm	psi KPa	
18.4-26 (480/80-26)	12	TL	W16L	56.3	18.8	36	36	11000	8800	156A8
				1430	478	29	250	5000	4000	
18.4-26 (480/80-26)	16	TL	W16L	56.3	18.8	36	45	13125	10500	162A8
				1430	478	29	310	5940	4750	
16.9-28 (440/80-28)	12	TL	W15L	55.5	17.2	34	38	9815	7850	152A8
				1410	437	27	260	4440	3550	
16.9-28 (440/80-28)	14	TL	W15L	55.5	17.2	34	44	10690	8550	155A8
				1410	437	27	300	4840	3875	
16.9-30 (420/85-30)	12	TL	W15L	57.5	17.1	34	34	10060	8050	153A8
				1461	434	27	235	4560	3650	
16.9-30 (420/85-30)	14	TL	W15L	57.5	17.1	34	45	11000	8800	156A8
				1461	434	27	310	5000	4000	
18.4-30 (460/85-30)	12	TL	W16L	60.2	18.5	36	36	11690	9350	158A8
				1529	470	29	250	5310	4250	
18.4-30 (460/85-30)	14	TL	W16L	60.2	18.5	36	42	12375	9900	160A8
				1529	470.0	29.0	290	5625	4500	