

MAXAM AGRIXTRA 65

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Extra wide profile 65-series tire for high flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951116	440/65R24	128D	TL	W14L	W13, W15L	17.4	442	46.5	1182	20	508	139.2	3534	37 575	53 42	172 78	51.5 195	18 x 2	190 1225
951201	480/65R24	133D	TL	W15L	W14L, DW14L, DW15L	18.9	479	48.6	1234	21.6	548	145.3	3690	38 600	54 43	198 90	52.3 198	18 x 2	217 1403
951217	540/65R24	140D	TL	W16L	DW16L, W18L, DW18L	20.9	530	51.7	1312	22	559	154.5	3923	39 625	58 46	247 112	80 303	18 x 2	264 1702
951119	420/65R28	128D	TL	W13	W11, W12	16.5	418	49.5	1257	21.2	538	148	3758	39 600	52 41	170 77	57 216	18 x 2	190 1225
951200	440/65R28	131D	TL	W14L	W13, DW14L, W15L, DW15L	17.4	442	50.5	1283	22.8	579	151.1	3836	39 625	53 42	190 86	47.3 179	18 x 2	206 1328
951202	480/65R28	136D	TL	W15L	W14L, DW14L, DW15L	18.9	479	52.6	1335	23.6	599	157.2	3992	40 650	54 43	216 98	58.6 222	18 x 2	236 1525
951203	540/65R28	142D	TL	W16L	DW16L, W18L, DW18L	20.9	530	55.6	1413	24.8	629	166.4	4225	41 675	58 46	271 123	77.1 292	19 x 2	280 1804



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951132	540/65R30	150D	TL	W16L	DW16L, W18L, DW18L	20.9	530	57.6	1464	25.8	655	172.4	4377	41 700	63 50	318 144	79.7 302	19 x 2	265 1711
951122	540/65R34	145D	TL	W16L	DW16L, W18L, DW18L	20.9	530	61.7	1566	25.9	658	184.4	4682	43 705	64 51	329 149	121.2 459	20 x 2	306 1974
V951149	600/65R34	151D	TL	DW20B	W18L	24.1	611	64.7	1644	29	736	193.6	4916	43 775	66 52	375 170	118.3 448	20 x 2	364.1 2349
951215	540/65R38	147D	TL	W16L	DW16L, W18L, DW18L	20.9	530	65.6	1667	27.5	698	196.3	4984	44 800	64 51	364 165	140.2 531	20 x 2	325 2094
951205	600/65R38	153D	TL	DW20B	W18L, DW18L, DW20A	24.1	611	68.7	1745	31	787	205.5	5218	45 825	66 52	401 182	129.4 490	20 x 2	385 2485
V951146	650/65R38	166D	TL	DW20B	DW20A	25.4	645	71.3	1810	32	812	213.1	5412	46 875	71 56	536 243	151.3 573	20 x 2	419 2706
951133	650/65R42	165D	TL	DW20B	DW20A	25.4	645	75.3	1912	34	863	225.1	5717	47 925	73 58	531 241	163.4 619	21 x 2	449 2894

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS **VF** / SERIES

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951533	VF650/65R42	170D	TL	DW21B	DW23B	25.6	650	75.3	1913	33.2	843	229.1	5820	47 925	74 59	559 254	160.6 608	21 x 2	595 3841

MAXAM **AGRIXTRA 65**

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Extra wide profile 65-series tire for high flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



AGRIXTRA 65 LOAD AND INFLATION

Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar
440/65R24	128D	5/10 LT	3210/1455	3625/1645	4055/1840	4485/2035	4905/2225	5335/2420	5955/2700					
		40/65			3020/1370	3330/1510	3650/1655	3970/1800						
480/65R24	133D	5/10 LT	3660/1660	4155/1885	4640/2105	5125/2325	5625/2550	6110/2770	6815/3090					
		40/65			3450/1565	3815/1730	4180/1895	4540/2060						
540/65R24	140D	5/10 LT	4455/2020	5040/2285	5635/2555	6230/2825	6825/3095	7420/3365	8270/3750					
		40/65			4190/1900	4630/2100	5070/2300	5515/2500						
420/65R28	128D	5/10 LT	3210/1455	3625/1645	4055/1840	4485/2035	4905/2225	5335/2420	5955/2700					
		40/65			3020/1370	3330/1510	3650/1655	3970/1800						
440/65R28	131D	5/10 LT	3475/1575	3935/1785	4400/1995	4860/2205	5325/2415	5790/2625	6450/2925					
		40/65			3265/1480	3615/1640	3960/1795	4300/1950						
480/65R28	136D	5/10 LT	3990/1810	4520/2050	5050/2290	5580/2530	6110/2770	6650/3015	7410/3360					
		40/65			3750/1700	4145/1880	4540/2060	4940/2240						
540/65R28	142D	5/10 LT	4720/2140	5345/2425	5975/2710	6605/2995	7230/3280	7860/3565	8765/3975					
		40/65			4445/2015	4905/2225	5380/2440	5845/2650						



AGRIXTRA 65 LOAD AND INFLATION

Continued

Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar
540/65R30	150D	5/10 LT	4145/1880	4695/2130	5250/2380	5800/2630	6360/2885	6915/3135	7310/3315	7705/3495	8105/3675	8500/3855		
		40/65			4565/2070	5050/2290	5525/2505	6010/2725	6350/2880	6705/3040	7045/3195	7385/3350		
540/65R34	145D	5/10 LT	5160/2340	5845/2650	6540/2965	7220/3275	7915/3590	8600/3900	9590/4350					
		40/65			4860/2205	5370/2435	5885/2670	6395/2900						
600/65R34	151D	5/10 LT	6140/2785	6955/3155	7775/3525	8600/3900	9415/4270	10230/4640	11410/5175					
		40/65			5775/2620	6395/2900	7000/3175	7605/3450						
540/65R38	147D	5/10 LT	5470/2480	6195/2810	6935/3145	7660/3475	8390/3805	9120/4135	10175/4615					
		40/65			5150/2335	5700/2585	6240/2830	6780/3075						
600/65R38	153D	5/10 LT	6495/2945	7365/3340	8225/3730	9095/4125	9955/4515	10825/4910	12070/5475					
		40/65			6120/2775	6760/3065	7410/3360	8050/3650						
650/65R38	166D	5/10 LT	7345/3330	8325/3775	9295/4215	10275/4660	11255/5105	12240/5550	12790/5800	13350/6055	13905/6305	14455/6555	15150/6870	15830/7180
		40/65			6915/3135	7640/3465	8370/3795	9095/4125	9515/4315	9925/4500	10340/4690	10750/4875	11255/5105	11685/5300
650/65R42	165D	5/10 LT	7565/3430	8565/3885	9580/4345	10585/4800	11600/5260	12600/5715	13635/6185	14075/6385	14815/6720	15255/6920	16150/7325	16590/7525
		40/65			7120/3230	7870/3570	8620/3910	9370/4250	10140/4600	10500/4750	11000/5000	11400/5150	12000/5450	12300/5600

AGRIXTRA 65 LOAD AND INFLATION



Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar
VF650/65R42	170D	5/10	8140/3685	9680/4400	10890/4950	12100/5500	13530/6160	14520/6600						
		40/65	7400/3350	8800/4000	9900/4500	11000/5000	12300/5600	13200/6000						

*LT = Low Torque