



MAXAM

AGRIXTRA 85

MS951R - R1W RADIAL DRIVE TIRE

Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- Radial tire construction
- Self-cleaning tread design
- Wide tread for maximized performance in the field
- Low pressure for minimum soil disturbance
- Premium rubber compounds reduce ozone cracking and weathering

Applications



Size	Alt Size	L.I./S.S.	Type	Rim	O.D.		S.W.		T.D.		R.C.	
					in	mm	in	mm	32nds	mm	in	mm
250/85R24	9.5R24	109A8/B	TL	W8	40.8	1035.0	9.9	251.0	48.0	38.0	122	3095
280/85R24	11.2R24	115A8/B	TL	W9	42.8	1086.0	11.5	292.0	50.0	40.0	128	3247
320/85R24	12.4R24	122A8/B	TL	W11	45.4	1154.0	13.0	329.0	52.0	41.0	136	3450
340/85R24	13.6R24	125A8/B	TL	W12	46.8	1188.0	13.9	353.0	53.0	42.0	140	3552
380/85R24	14.9R24	131A8/B	TL	W13	49.5	1256.0	15.4	390.0	54.0	43.0	148	3755
420/85R24	16.9R24	137A8/B	TL	W15L	52.1	1324.0	17.2	438.0	58.0	46.0	156	3959
280/85R28	11.2R28	118A8/B	TL	W10	46.7	1187.0	11.5	292.0	50.0	40.0	140	3549
320/85R28	12.4R28	124A8/B	TL	W11	49.4	1255.0	13.0	329.0	52.0	41.0	148	3752
340/85R28	13.6R28	127A8/B	TL	W12	50.8	1289.0	13.9	353.0	53.0	42.0	152	3854
380/85R28	14.9R28	133A8/B	TL	W13	53.4	1357.0	15.4	390.0	54.0	43.0	160	4057
420/85R28	16.9R28	139A8/B	TL	W15L	56.1	1425.0	17.2	438.0	58.0	46.0	168	4261
380/85R30	14.9R30	135A8/B	TL	W13	55.4	1408.0	15.4	390.0	54.0	43.0	166	4210
420/85R30	16.9R30	140A8/B	TL	W15L	58.1	1476.0	17.2	438.0	63.0	50.0	174	4413
460/85R30	18.4R30	145A8/B	TL	W16L	60.8	1544.0	18.7	475.0	64.0	51.0	182	4617
320/85R32	12.4R32	126A8/B	TL	W11	53.4	1357.0	13.0	329.0	52.0	41.0	160	4057
380/85R34	14.9R34	146A8/B	TL	W12	59.5	1510.0	15.0	380.0	54.0	43.0	160	4515
420/85R34	16.9R34	142A8/B	TL	W15L	62.1	1578.0	17.2	438.0	63.0	50.0	186	4718
460/85R34	18.4R34	147A8/B	TL	W16L	64.8	1646.0	18.7	475.0	64.0	51.0	194	4922
320/85R36	12.4R36	128A8/B	TL	W11	57.4	1458.0	13.0	329.0	52.0	41.0	172	4359
340/85R36	13.6R36	132A8/B	TL	W12	58.8	1492.0	13.9	353.0	58.0	46.0	176	4461
340/85R38	13.6R38	133A8/B	TL	W12	60.8	1543.0	13.9	353.0	58.0	46.0	182	4614
380/80R38	14.9R38	142A8/B	TL	W12	61.9	1573.0	15.0	380.0	57.0	45.0	160	4703
420/85R38	16.9R38	144A8/B	TL	W15L	66.1	1679.0	17.2	438.0	63.0	50.0	198	5020
460/85R38	18.4R38	149A8/B	TL	W16L	68.8	1747.0	18.7	475.0	64.0	51.0	206	5224
520/85R38	20.8R38	155A8/B	TL	W18L	72.8	1849.0	21.1	536.0	67.0	53.0	218	5529
460/85R42	18.4R42	156A8/B	TL	W16L	72.7	1846.0	18.7	475.0	64.0	51.0	217	5520
480/80R42	18.4R42	151A8/B	TL	W16L	72.8	1849.0	19.3	489.0	64.0	51.0	218	5529
520/85R42	20.8R42	157A8/B	TL	DW18L	76.8	1951.0	21.1	536.0	67.0	53.0	230	5833
520/85R42	20.8R42	166A8/B	TL	DW18L	76.8	1951.0	21.1	536.0	67.0	53.0	230	5833
480/80R46	18.4R46	158A8/B	TL	W16A	76.2	1936.0	19.3	489.0	64.0	51.0	228	5789
520/85R46	20.8R46	158A8/B	TL	W16A	80.8	2052.0	20.3	516.0	69.0	55.0	242	6135
480/80R50	18.4R50	159A8/B	TL	DW16A	80.8	2051.0	19.3	489.0	64.0	51.0	242	6132
480/80R50	18.4R50	176A8/B	TL	DW16A	80.3	2038.0	19.3	489.0	64.0	51.0	240	6094