


GALAXY EARTH-PRO RADIAL 700 R-1W



Galaxy Earth-Pro Radial 700 series tire has advanced lug design with steep angle in center for smooth ride, long wear and self-cleaning. It has a lower angle at shoulder for traction. This tire provides greatly improved hillside stability. The Galaxy Earth-Pro Radial 700 tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



Size	Type	PR	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
300/70R20	120A8/120B	TL	W9	956	293	2877	438.1	1400	2.4	40
				37.6	11.5	113.2	17.2	3086	35	25
320/70R20	123A8/123B	TL	W10	986	325	2908	445	1550	2.4	40
				38.8	12.8	114.5	17.5	3417	35	25
280/70R20	116A8/116B	TL	W10	912	278	2706	415	1250	2.4	40
				35.9	10.9	106.5	16.3	2756	35	25
320/70R24	116A8/116B	TL	W10	1094	319	3260	504.9	1250	1.6	40
				43.0	12.5	128.3	19.8	2756	23	25
360/70R24	122A8/122B	TL	W11	1152	357	3360	511.5	1500	1.6	40
				45.3	14.0	132.2	20.1	3307	23	25
380/70R24	125A8/125B	TL	W12	1191	381	3510	538	1650	1.6	40
				46.9	15	138.2	21.2	3638	23	25
420/70R24	130A8/130B	TL	W13	1248	419	3668	551.5	1900	1.6	40
				49.1	16.5	144.4	21.7	4189	23	25
480/70R24	138A8/138B	TL	W15L	1316	479	3859	588	2360	1.6	40
				51.8	18.9	151.9	23.1	5203	23	25
320/70R28	119A8/119B	TL	W10	1191	320	3515	546	1360	1.6	40
				46.9	12.6	138.4	21.5	2998	23	25
360/70R28	125A8/125B	TL	W11	1240	358	3658	572	1650	1.6	40
				48.8	14.1	144	22.5	3638	23	25
380/70R28	127A8/127B	TL	W12	1293	380	3744	578.5	1750	1.6	40
				50.9	14.9	147.4	22.7	3858	23	25
420/70R28	133A8/133B	TL	W13	1349	418	3938	594.4	2060	1.6	40
				53.1	16.4	155.0	23.4	4542	23	25
480/70R28	151A8/145E	TL	W15L	1415	480	4173	640	2500	1.6	40
				55.7	18.9	164.3	25.2	5512	23	25
520/70R30	145A8/145B	TL	W16L	1536	516	4475	668	3450	1.5	40
				60.4	20.3	176.1	26.2	7606	23	25
420/70R30	134A8/134B	TL	W13	1398	418	4124.96	626.1	2120	1.6	40
				55	16.4	162.4	24.6	4674	23	25
480/70R30	141A8/141B	TL	W15L	1478	479	4359	657.7	2575	1.6	40
				58.2	18.8	171.6	25.8	5677	23	25
480/70R34	143A8/143B	TL	W15L	1580	480	4661	719	2725	1.6	40
				62.2	18.9	183.5	28.3	6008	23	25
520/70R34	148A8/148B	TL	W16L	1640	516	4783	720.4	3150	1.6	40
				64.6	20.3	188.3	28.3	6945	23	25
480/70R38	145A8/145B	TL	W15L	1681	479	4965	751.4	2900	1.6	40
				66.2	18.8	195.4	29.5	6393	23	25
520/70R38	150A8/150B	TL	W16	1749	516	5163	750.5	3348	1.6	40
				68.8	20.3	203.2	29.5	7381	23	25
710/70R38	172A8/172B	TL	DW23B	1958	716	5768	880	6300	2.4	40
				77.1	28.2	227.1	34.6	13889	35	25
580/70R38	155A8/155B	TL	W18L	1827	577	5502	819.1	3875	1.6	40
				71.9	22.7	216.6	32.2	8543	23	25
710/70R42	173A8/173B	TL	DW23B	2061	716	6153	937.5	6500	2.4	40
				81.1	28.2	242.2	36.9	14330	35	25