


RADIAL TRACTOR

GALAXY EARTH-PRO RADIAL 850 R-1W



Galaxy Earth-Pro Radial 850 tire has an advanced lug design with steep angle in center for smooth ride, long wear and self cleaning. It has a lower angle at shoulder for traction. This tire provides greatly improved hillside stability. The Galaxy Earth-Pro Radial 850 tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



Size	LI	Type	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
280/85R20	112A8/112B	TL	W10	990	288	2950	450.6	1120	1.6	50
				38.9	11.3	116.1	17.7	2469	23	31
320/85R20	119A8/119B	TL	W11	1052	329	3042	466	1360	1.6	40
				41.4	13	119.7	18.3	2998	23	25
250/85R24	109A8/109B	TL	W8	1037	246	3026	474	1030	1.6	40
				40.8	9.7	119.1	18.6	2271	23	25
280/85R24	115A8/115B	TL	W11	1086	282	3159	491	1215	1.6	40
				42.8	11.1	124.3	19.3	2679	23	25
320/85R24	122A8/122B	TL	W11	1148	336	3368	513.3	1500	1.6	40
				45.2	13.2	132.5	20.2	3307	23	25
340/85R24	125A8/125B	TL	W12	1181	356	3452	525	1650	1.6	40
				46.5	14	135.9	20.6	3638	23	25
380/85R24	131A8/131B	TL	W12	1245	391	3610	549.2	1950	1.6	40
				49	15.3	142.1	21.6	4299	23	25
420/85R24	137A8/137B	TL	W15L	1315	418	3835	591	2300	1.6	40
				51.8	16.5	151	23.3	5071	23	25
280/85R28	118A8/118B	TL	W9 W10	1190	280	3564	544.3	1320	1.6	40
				46.9	11	140.3	21.4	2910	23	25
320/85R28	124A8/124B	TL	W11	1246	325	3734	565	1600	1.6	40
				49.1	12.8	147	22.2	3527	23	25
380/85R28	133A8/133B	TL	W12	1352	380	3988	604	2060	1.6	40
				53.2	15	157	23.8	4542	23	25
420/85R28	139A8/139B	TL	W15L	1420	418	4049	627.4	2430	1.6	40
				55.9	16.5	159.4	24.7	5357	23	25
340/85R28	127A8/127B	TL	W12	1289	343	3785	580	1750	1.6	40
				50.7	13.5	149	22.8	3858	23	25
460/85R30	145A8/145B	TL	DW15L	1524	478	4509	684	2900	1.6	40
				60	18.8	177.5	26.9	6393	23	25
380/85R30	135A8/135B	TL	W12	1408	380	4111	676.5	2180	1.6	40
				55.4	15	161.8	26.6	4806	23	25
420/85R30	140A8/140B	TL	W15L	1468	431	4343	658	2500	1.6	40
				57.8	17	171	25.9	5512	23	25
420/90R30	147A8/147B	TL	W13	1518	418	4445	684	3075	2.4	40
				59.8	16.5	175	26.9	6779	35	25
420/90R30	142A8/142B	TL	W13	1518	418	4445	684	2650	1.6	40
				59.8	16.5	175	26.9	5842	23	25
320/85R32	126A8/126B	TL	W11	1052	329	3013	609.1	1701	1.6	50
				41.4	12.9	118.6	23.9	3750	23	31
420/85R34	142A8/142B	TL	W13	1578	418	4636	706.5	2650	1.6	40
				62.1	16.4	182.5	27.8	5842	23	25
460/85R34	147A8/147B	TL	DW15L	1637	479	4815	740.5	3075	1.6	40
				64.4	18.9	189.5	29.1	6779	23	25
380/85R34	137A8/137B	TL	W12	1510	380	4441	676.5	2300	1.6	40
				59.4	15	174.8	26.6	5071	23	25

Size	LI	Type	RIM	OD	SW	RC	SLR	Recommended Load	Inflation Pressure	Speed
				mm in	mm in	mm in	mm in	kg lbs	bar psi	kmph mph
320/85R36	128A8/128B	TL	W11	1458	325	4371	675	1800	1.6	40
				57.4	12.8	172	26.6	3968	23	25
340/85R36	132A8/132B	TL	W12	1495	345	4425	689	2000	1.6	40
				58.9	13.6	174.2	27.1	4409	23	25
340/85R38	133A8/133B	TL	W12	1543	345	4567	714	2060	1.6	40
				60.7	13.6	179.8	28.1	4542	23	25
420/85R38	144A8/144B	TL	W15L	1679	418	4903	750	2800	1.6	40
				66.1	16.4	193	29.5	6173	23	25
460/85R38	149A8/149B	TL	W16L	1747	455	5105	778.4	3250	1.6	40
				68.7	17.9	200.9	30.6	7165	23	25
520/85R38	155A8/155B	TL	W16L	1849	516	5394	819.3	3875	1.6	40
				72.7	20.3	212.3	32.2	8543	23	25
320/85R38	143A8/143B	TL	W11	1509	325	4532	701	2725	3.6	40
				59.4	12.8	178.4	27.6	6008	52	25
380/80R38	142A8/142B	TL	W12	1578	375	4721	728	2650	2.4	40
				62.1	14.8	185.9	28.7	5842	35	25
480/80R42	151A8/151B	TL	DW16L	1835	479	5461	841	3450	1.6	40
				72.2	18.9	215	33.1	7606	23	25
520/85R42	157A8/157B	TL	DW16L	1951	516	5788	881.5	4125	1.6	40
				76.8	20.3	227.8	34.7	9094	23	25
320/80R42	141A8/141B	TL	W10	1580	319	4676	739	2575	3.2	40
				62.2	12.6	184.1	29.1	5677	46	25
320/90R42	147A8/147B	TL	W10	1643	319	4940	764	3075	3.6	40
				64.7	12.6	194.5	30.1	6779	52	25
480/80R46	158A8/158B	TL	DW16L	1960	479	5791	880	4250	1.6	40
				77.2	18.9	228	34.6	9370	23	25
520/85R46	158A8/158B	TL	DW16L	2052	516	6096	937	4250	1.6	40
				80.8	20.3	240	36.9	9370	23	25
320/90R46	148A8/148B	TL	W10	1744	319	5258	815	3150	3.6	40
				68.7	12.6	207	32.1	6945	52	25
380/90R46	165A8/165B	TL	W12	1863	380	5582	860	4875	4.7	40
				73.3	15	219.8	33.9	10748	68	25

Size	Rim	Unloaded Dimension		Loaded Static radius	RC	Load Index PR Symbols	Recommended Load												
		SW	OD				Speed										Inflation Pressure	Cyclic operation	
							1)Not high and sustained torque, 2)Road Transport											bar psi	10
		Non cyclic operation										bar psi	Cyclic operation						
		mm in	mm in				mm in	mm in	mm in	bar psi	Static kmph		10 kmph	15 kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph
280/85R20 (11.2R20)	W10X20	288	990	450.6	2950	112A8	1.6	2580	1680	1500	1240	1200	1120	1120	2	1900	1740		
		11.3	39	17.7	116.1	112B	23	5688	3704	3307	2734	2646	2469	2469	29	4189	3836		