

# GALAXY FLOT PRO 1-3



Galaxy FLOT PRO is specially designed for low end applications like balers,wagons and other agricultural implements.It displays excellent flotation and self cleaning characteristics. The tire has moderate traction flotation profile and provides maximum soil protection and low soil compaction.



Size	Rim	Unloaded Dimension		Loaded Static radius	RC	Load Index PR Symbols	Inflation Pressure	Recommended Load							
		SW	OD					Speed				Free Rolling			
		mm	mm	10	25			40	50	10	25	40	50		
		in	in	mm	mm			mm	mm	mm	mm	mm	mm		
260/75-15.3	9	268	784	343	2260	12	4.7	1650	1400	1180	1062	2380	2020	1700	1530
		10.5	30.8	13.5	89	126A8	68	3640	3090	2600	2340	5250	4450	3750	3370
400/60-15.5	13.00DC	404	874	377	2510	16	4.4	3140	2670	2240	2016	4410	3750	3150	2840
		15.9	34.4	14.8	98.8	148A8 144B	64	6920	5890	4940	4450	9720	8270	6950	6260
15.0/70-18IMP	W13X18	391	990	420.9	2992	16	4.25					4451	3692	3105	
	13.00X18	15.4	39	16.6	117.8	151A6 148A8	62					9813	8139	6845	
500/45-22.5	16.00DC	500	1030	455	3153	16	3.6	3710	3150	2650	2385	5250	4460	3750	3375
		19.7	40.6	17.9	124.1	154A8	52	8180	6950	5840	5260	11570	9830	8270	7440
500/60-22.5	16.00DC	500	1170	510	3460	16	4.4	6910	5880	4930	4450	8200	6960	5850	5270
		19.7	46.1	20.1	136.2	163A8	64	15230	12960	10870	9810	18080	15340	12900	11620
550/45-22.5	16.00DC	550	1070	470	3105	16	2.8	4310	3660	3075	2770	6130	5210	4375	3940
	18.00DC	21.7	42.1	18.5	122.2	159A8	41	9500	8070	6780	6110	13510	11490	9650	8690
550/60-22.5	16.00DC	550	1238	540	3765	16	3	5250	4460	3750	3380	7420	6310	5300	4770
		21.7	48.7	21.3	148.2	166A8	44	11570	9830	8270	7450	16360	13910	11680	10520
600/50-22.5	16.00DC	600	1170	520	3450	16	2.6	5110	4340	3650	3285	7210	6130	5150	4640
		23.6	46.1	20.5	135.8	165A8	38	11270	9570	8050	7240	15900	13510	11350	10230