



MAXAM

MS903

BACKHOE INDUSTRIAL SERVICE

Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	Rating	Type	Rim	O.D.		T.D.	L.I.	Infl. P.	Load Capacity (kg/lbs)	
				mm inch	mm inch				kPa psi	10 km/h 5 mph
18.4-26 (480/80-26)	12	TL	W16L	1430	478	29	156A8	36	5000	4000
				56.3	18.8	36/32			11000	8800
	16	TL	W16L	1430	478	29	162A8	45	5940	4750
				56.3	18.8	36/32			13125	10500
16.9-28 (440/80-28)	12	TL	W15L	1410	437	27	152A8	38	4440	3550
				55.5	17.2	34/32			9815	7850
	14	TL	W15L	1410	437	27	155A8	44	4840	3875
				55.5	17.2	34/32			10690	8550
16.9-30 (420/85-30)	12	TL	W15L	1461	434	27	153A8	34	4560	3650
				57.5	17.1	34/32			10060	8050
	14	TL	W15L	1461	434	27	156A8	45	5000	4000
				57.5	17.1	34/32			11000	8800
18.4-30 (460/85-30)	12	TL	W16L	1529	470	29	158A8	36	5310	4250
				60.2	18.5	36/32			11690	9350
	14	TL	W16L	1529	470	29	160A8	42	5625	4500
				60.2	18.5	36/32			12375	9900

