

E3/L3



ALL GRIP+

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting. Excellent traction in all off-road conditions. Thick undertread for improved puncture resistance. High quality carcass allows for excellent retreadability. Wear and cut resistant tread compound. Wide, flat footprint profile for maximum stability and wear. Increased net-to-gross for improved tread life.

Engineered for:
Loaders \ Dump Trucks \ Graders



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 mph	
17.5R25	**	TL	14.00/1.5	52.7	17.7	35	94	18700	76	12000	182A2/167B
				1338	450	28	650	8500	525	5450	
20.5R25	**	TL	17.00/2.0	59.0	20.4	38	94	25400	76	16100	193A2/177B
				1498	518	30	650	11500	525	7300	
23.5R25	**	TL	19.50/2.5	63.4	23.9	42	94	32000	76	20400	201A2/185B
				1610	607	33	650	14500	525	9250	
26.5R25	**	TL	22.00/3.0	68.8	26.7	45	94	40800	76	25400	209A2/193B
				1747	678	36	650	18500	525	11500	
29.5R25	**	TL	25.00/3.5	74.3	30.0	49	94	49400	76	30900	216A2/200B
				1887	762	39	650	22400	525	14000	

