

AGRO INDUSTRIAL



BIAS TIRES BUILT FOR AG/INDUSTRIAL APPLICATIONS

X Tread compound provides high resistance against wear and cuts | Wide lugs & tread width provide excellent stability and smooth ride on hard surfaces | Strong casing provides resistance to impacts and shocks in heavy-duty operations | Center tie bar design for better lug stability to eliminate lug base cracks

Tire Size	PR	TT/TL	Rim		Unloaded Inflated Dimension $\pm 2\%$		SLR	RC $\pm 2.5\%$	Maximum Load @30kmph (20 mph)			Maximum Load @40kmph (25 mph)			Inflation Pressure	Tread Depth					
			Rec.	Alt.	S.W.	O.D.			mm	mm	mm	mm	kgs	Speed Symbol			Load Index	kgs	Speed Symbol	Load Index	kgs
10.0/75-15.3	10	TL	9	-	264	780	356	2286	A6	128	1800	A8	123	1550	3.9	23					
11.5/80-15.3	12	TL	9	-	290	866	381	2540	A6	139	2450	A8	135	2180	4.1	24					
11.5/80-15.3	14	TL	9	-	290	866	381	2540	A6	143	2725	A8	139	2430	4.8	24					
15.0/55-17	10	TL	13	13	381	889	406	2616	A6	141	2575	A8	134	2120	2.6	24					
10.5/80-18	10	TL	W9	W8	274	907	406	2667	A6	138	2360	A8	131	1950	5.0	23					
12.5/80-18	12	TL	W9	11	307	988	432	2896	A6	146	3000	A8	142	2650	3.7	28					