




SUSTAINABLE PERFORMANCE

MAXAM

MS700

INDUSTRIAL PRO

Applications:



High performance Super Premium three-stage solid resilient tire featuring a full-size tread profile for excellent traction, stability, and tire life.

- Produced with EcoPoint3 rubber compounding technology, with exceptional resistance to wear and chunking
- Unique tread for an optimal combination of traction and tread life
- Smooth centerline design provides smooth ride, enhanced steering, and prevents chunking in aggressive applications
- Incorporates a superior center compound with unmatched heat resistance and shock absorption for the most demanding industrial applications
- Widest footprint in its class for maximum lifting capabilities

Size	Rim	Type		O.D.		S.W.		T.D.		L.C.C. (lbs/kg)	
		STD	SWIFT	in.	mm	in.	mm	in.	mm	15 mph/25 kph	
										Load Wheels	Steer Wheels
15x4.5-8 (125/75-8)	3.00D	*	*	14,90	378	4,45	113	1,14	29	2295/1040	1765/800
	3.25I	*	*	14,90	378	4,45	113	1,14	29	2295/1040	1765/800
16x6-8 (150/75-8)	4.33R	*	*	16,20	411	6,00	152	1,30	33	3210/1455	2470/1120
5.00-8	3.00D	*	*	18,00	457	4,8	121	1,43	36	3120/1415	2405/1090
18x7-8 (180/70-8)	4.33R	*	*	18,00	457	6,1	155	1,48	38	4730/2145	3640/1650
140/55-9	6.00E	*	*	14,90	378	5,04	128	1,10	28	2580/1170	1985/900
6.00-9	4.00E	*	*	20,75	527	5,5	140	1,88	48	4155/1885	3200/1450
21x8-9 (200/75-9)	6.00E	*	*	20,30	516	7,30	185	1,97	50	6075/2755	4675/2120
200/50-10	6.50F	*	*	18,00	457	7,60	193	1,56	40	5445/2470	4190/1900
6.50-10	5.00F	*	*	22,50	572	6,5	165	2,00	51	5160/2340	3970/1800
23x9-10 (225/75-10)	6.50F	*	*	23,00	584	7,9	201	2,15	55	7595/3445	5840/2650
23x10-12 (250/60-12)	8.00G	*	*	23,00	584	9,20	234	2,17	55	8310/3770	6395/2900
315/45-12	10.00	*	*	23,00	584	11,10	282	2,17	55	9890/4485	7605/3450
7.00-12	5.00S	*	*	25,60	650	6,7	170	2,20	56	6440/2920	4940/2240
27x10-12 (250/75-12)	8.00G	*	*	26,60	676	9,65	245	2,50	64	8600/3900	6610/3000
7.00-15	5.50	*	*	28,80	732	7,1	180	2,23	57	7815/3545	6010/2725
	6.00	*	*	28,80	732	7,1	180	2,23	57	7815/3545	6010/2725
28x9-15 (8.15-15)	7.00	*	*	27,30	693	8,5	216	1,95	50	8600/3900	6615/3000
250-15 (250/70-15)	7.00	*	*	28,10	714	8,7	221	2,07	53	10230/4640	7870/3570
	7.50	*	*	28,10	714	8,7	221	2,07	53	10230/4640	7870/3570
28x12.5-15 (355/45-15)	9.75	*	*	28,00	711	11,23	285	2,20	56	12180/5525	9370/4250
8.25-15	6.50	*	*	32,00	813	10,0	254	2,54	65	10470/4750	8050/3650
300-15 (315/70-15)	8.00	*	*	32,00	813	10,0	254	2,54	65	12895/5850	9920/4500
355/65-15 (350-15)	9.75	*	*	32,00	813	12,30	312	3,46	88	17195/7800	13230/6000
400/60-15	11.00	*	*	32,13	816	12,95	329	3,31	84	19775/8970	15210/6900
10.00-20	7.00	*	*	40,40	1026	9,5	241	3,17	81	13230/6000	11025/5000
	7.50	*	*	40,40	1026	9,5	241	3,17	81	13230/6000	11025/5000
	8.00	*	*	40,40	1026	9,5	241	3,17	81	13230/6000	11025/5000
12.00-20	8.00	*	*	42,90	1090	11,0	279	3,40	86	16660/7560	13890/6300
	8.50	*	*	42,90	1090	11,0	279	3,40	86	16660/7560	13890/6300
	10.00	*	*	42,90	1090	11,0	279	3,40	86	17190/7800	14330/6500
12.00-24	8.50	*	*	47,00	1194	11,7	297	3,40	86	17720/8040	14770/6700
	10.00	*	*	47,00	1194	11,7	297	3,40	86	19840/9000	16535/7500
14.00-24	10.00	*	*	52,0	1321	12,8	325	4,3	108	24470/11100	20390/9250
	10.00/1.5	*	*	52,0	1321	12,8	325	4,3	108	24470/11100	20390/9250
14.00-25	11.25/1.5	*	*	52,0	1321	12,8	325	4,3	108	24470/11100	20390/9250
	11.25/2.0	*	*	56,89	1445	15,9	405	4,96	126	33740/15305	24430/11080
18.00-25	13.00/2.5	*	*	63,50	1613	18,4	467	6,02	153	44800/20320	32440/14715